


Specificatie vacuümbuis collector

Vacuümbuis collector	Solesta 20v	Solesta 25v	Solesta 30v
Algemeen			
Vermogen	1165w	1457w	1748w
Opbrengst	3,7GJ	4,2GJ	4,7GJ
Collector oppervlak	3,03m ²	3,77m ²	4,50 m ²
Minimale hellingshoek	20°	20°	20°
Maximale hellingshoek	80°	80°	80°
Gewicht	65 kg	82 kg	108 kg
Minimale temperatuur	-20°C	-20°C	-20°C
Stagnatie temperatuur	221°C	221°C	221°C
	6NTO1L	6NTO1L	6NTO1L
Collector			
Inhoud	0,59 l	0,73 l	0,87 l
Debiet	20 l /h	25 l /h	30 l /h
Materiaal	koper/glas	koper/glas	koper/glas
Frame			
Materiaal	Aluminium zwart	Aluminium zwart	Aluminium zwart
Aansluitingen			
Aanvoer (warm)	10 mm opsteek	10 mm opsteek	10 mm opsteek
Retour (koud)	10 mm opsteek	10 mm opsteek	10 mm opsteek
Afmetingen			
Lengte	1,96 m	1,96 m	1,96 m
Breedte	1,55 m	1,93 m	2,30 m
Hoogte (afstand pan>collector)	0,15 m	0,15 m	0,15 m

 Meer informatie?

 024-35 40 46 5

SOLESTA[®]
Zonneboilers

www.solesta.nl